CSC2K.GB/02/05.07

FLEXDRAIN®

TEMPERATURE MAINTENANCE SYSTEMS



www.flexelec.com

CE **CSC2K - Silicon elastomer insulated drain-line heaters** with integrated thermostat

Characteristics

- Integrated thermostat.
- · Fully sealed.
- Double insulation.
- Extremely flexible.
- Voltage 230 V as standard.
- Power cable: length 1 m as standard.

Heating section

accessories

Use

36

Applications

CSC2K heaters are designed to be placed at the bottom of collector trays inside refrigeration equipment in cold rooms, to prevent freezing and to allow condensate water to flow freely.

The integrated thermostat makes them fully autonomous.

Note: The most commonly used power rating is 50 W/m. However, for plastic trays, we strongly recommend using the 40W/m range.

Wire terminated in the cold tail

Black mark

Silicon elastomer insulation

Silicon elastomer insulation Heating wire Fibre glass core Conductor cable

Standard models

	CSC2K	
Length (m)	40 W/m	50 W⁄m
1	40 W	50 W
1.3	52 W	65 W
1.5	60 W	75 W
2	80 W	100 W
3	120 W	150 W
4	160 W	200 W
5	200 W	250 W
6	240 W	300 W

		CSC2K
Termination 18 x 16 mm with thermostat	Heating wire	Nickel-Chrome or Nickel-Copper
	Insulation	Silicon elastomer
	Section	5 x 7 mm
Caution	Power	40 or 50 W/m
These cables must never be cut to shorten the cold tail. The round part of the thermostat (sensor) must be placed in the best position to collect information so that the cable can operate as required.	Max. voltage	500 V
	Permissible surface temperature	from - 40°C to + 110°C
se	Tolerances	Power: ± 10 % Section: + 0.2 / - 0.1 mm Length: ± 1 %
Drain-line cables are series resistors. Consult the pages of the catalogue devoted to the corresponding general	End insulation	Heat-shrink sheath with adhesive Pre-set to + 5°C/+ 15°C
an existing principles across the instructions for use and	Thermostat	Pre-set to + 3 6/ + 13 6

Pre-set to + 5°C/+ 15°C

FLEXELEC S.A.S

10, rue des frères Lumière Z.A. du Bois Rond 69720 ST BONNET DE MURE - FRANCE Tel: + 33 (0)4.72.48.30.90 Fax: + 33 (0)4.78.40.82.81 F-mail: flexelec@omerin.com

operating principles, general instructions for use and

FLEXELEC Dept

OMERIN ASIA Pte Ltd 51 Goldhill Plaza #08-12/01 SINGAPORE 308900 Tel: + 65.6255.4778 Fax: + 65.6255.4779 F-mail: sales@omerin.com.sg

FLEXELEC (UK) Ltd PLEXELEC (UN) Lta Unit 11 Kings Park Industrial Estate Primrose Hill - KINGS LANGLEY Hertfordshire - WD4 8ST - UK Tel: + 44 (0) 1923.270477 Fax: + 44 (0) 1923.270264

E-mail: sales@omerin.co.uk

FLEXELEC Dept

FLEXELEC Dept OMERIN GmbH Tennweg 2 B D-65510 IDSTEIN - GERMANY Tel: + 49 (0) 6126.94.31-0 Fax: + 49 (0) 6126.83.99 E-mail: omeringmbh@omerin.com