FLEXTRACE®



TEMPERATURE MAINTENANCE SYSTEMS

www.flexelec.com

FTSH - FTSH/T - FTSH/I - FTSH/TF Silicon elastomer insulated constant power cables





Characteristics

- Welded contact points.
- Hard-wearing and flexible.
- Can be cut to length on site.
- Extremely simple termination.
- Cold tail incorporated: no extra connection necessary.
- Available as 20, 30 or 40 W/m.
- Power supply: 230 V as standard (115 V and 400 V on request).
- : silicon elastomer insulated constant power cables.
- FTSH/T : with tinned copper braid for mechanical protection
 - and earthing.
- FTSH/I : with stainless steel braid for mechanical protection
 - and earthing.
- FTSH/TF: with tinned copper braid and fluoropolymer
 - anti-corrosion outer sheath.

Applications

FTSH cables are particularly suitable for maintaining temperatures of up to + 150°C.

Its great flexiblity down to - 70°C means that this version is ideal for heat tracing in industrial refrigeration or in countries with very harsh climates.

To ensure that these heating elements enjoy a long service life, we recommend using a control device.



11/11			
	11	//	
		all b	1

Power	Distance between 2 consecutive contact points	Max. circuit length	Max. maintenance temperature
20 W/m	0.7 m	140 m	150°C
30 W/m	0.7 m	120 m	140°C
40 W/m	0.6 m	100 m	120°C

Tinned copper conductor 2 mm²

Silicon elastomer insulation

Welded contact point

Heating wire

Silicon elastomer insulation

Metal braid (FTSH/T, FTSH/I, FTSH/TF)

Fluoropolymer outer sheath (FTSH/TF)

Heating wire
Dimensions
FTSH
FTSH/T - FTSH/I
FTSH/TF
Power
Conductor insulation
Heating wire insulation
Outer sheath
Permissible surface temperature

FTSH	
Nickel-Copper or Nickel-Chrome	
6 x 10 mm	
6.5 x 10.5 mm	
7 x 10 mm	
20, 30 or 40 W/m	
Silicon elastomer	
Silicon elastomer	
Fluoropolymer	
from - 70°C to + 200°C	

Consult the pages of the catalogue devoted to the corresponding general operating principles, general instructions for use and accessories.

FLEXELEC S.A.S

10, rue des frères Lumière Z.A. du Bois Rond 69720 ST BONNET DE MURE - FRANCE Tel: + 33 (0)4.72.48.30.90 Fax: + 33 (0)4.78.40.82.81

FLEXELEC Dept

OMERIN ASIA Pte Ltd 51 Goldhill Plaza #08-12/01 SINGAPORE 308900 Tel: +65.6255.4778 Fax: +65.6255.4779 F-mail: sales@omerin.com.sq

FLEXELEC (UK) Ltd

Unit 11 Kings Park Industrial Estate Primrose Hill - KINGS LANGLEY Hertfordshire - WD4 8ST - UK Tel: + 44 (0) 1923.274477 Fax: + 44 (0) 1923.270264 F-mail: sales@omerin.co.uk

FLEXELEC Dept

OMERIN GmbH Tennweg 2 B D-65510 IDSTEIN - GERMANY Tel: + 49 (0) 6126.94.31-0 Fax: + 49 (0) 6126.83.99 E-mail: omeringmbh@omerin.com